







Aquacon 345

Polyfabric

FLOATING COVERS

ALGAE & AQUACULTURE PONDS AND TANKS

DAM, POND AND CHANNEL LINERS





Aquacon[™] 345 is a premium polyethylene scrim reinforced polyfabric, specifically designed for **floating cover** and **liner applications**.

Lightweight, flexible and durable Aquacon™ 345 exhibits class leading welding characteristics, providing effective and efficient field welding performance, ideal for in-factory fabrication and deployment on-site.

The high strength woven HDPE scrim reinforcement and engineered UV-stabilised polyethylene coatings provide outstanding puncture and abrasion resistance to withstand the harshest of installation and environmental conditions.



- Light weight polyethylene enables large liner sections to be prefabricated for speedy installation on-site
- Woven scrim reinforcement provides dimensional stability and high puncture, tear and tensile performance properties
- Engineered polyethylene coatings provide superior abrasion resistance, UV-resistance and excellent chemical resistance
- GALE Pacific's advanced coating technology results in excellent welding and layflat characteristics for easy pre-fabrication and efficient in-field installation
- Flexible coating requires no polymeric or liquid plasticisers, eliminating chemical leaching
- 100% recyclable material ensures minimal impact on the environment with no chlorine or heavy metals in the product



Properties

Nominal fabric mass 345gsm ± 10
Thickness (mean) (mm) 0.45mm
Roll length (m) Jumbo (1,200 – 1,400m)
Roll width (m) 2.05 width

Performance

Tensile strength - warp 1516N / 50mm
Elongation at break - warp 19.5%

Tensile strength - weft 1485N / 50mm
Elongation at break - weft 20.5%

Wing tear - warp (mean) 135N


Wing tear - weft (mean) 137N

Bursting strength 3300kPa

Hydrostatic pressure (mean) >250kPa

Applications

- Floating covers
- Algae & aquaculture ponds and tanks
- Dam, pond and channel liners
- Agriculture pits and ponds
- Bunding, baffle curtains and containment booms
- Biogas containment
- Tank liners





NZ P 0800 555 171

UAE P +971 4 881 7114

USA P 1800 560 4667